

# ABS MUL HT<sup>†</sup>



## BENEFITS

- Performs at temperatures up to 450°F
- Effective without the need for a secondary emulsifier package
- Effective at low concentrations



## APPLICATIONS

- Performs as part of the ABS 40 system and other invert emulsion drilling fluid systems
- 1.0 gal/bbl (typical) for most applications



## PHYSICAL PROPERTIES

- Appearance: Dark amber liquid
- Specific Gravity: 0.93
- Flash Point: >250°F

ABS MUL HT is a concentrated emulsifier package for high temperature applications.



ABS MUL HT emulsifier

## TREATMENT RECOMMENDATIONS

Typical concentrations of 1 gallon per barrel are sufficient for most applications. ABS MUL HT mixes easily with minimal agitation.

## PACKAGING AND HANDLING

ABS MUL HT is available in 275 gal totes. Handle ABS MUL HT as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



# **AES DRILLING FLUIDS**

[www.aesfluids.com](http://www.aesfluids.com)

☎ Phone : 281 556 5628

✉ Email : [info@aesfluids.com](mailto:info@aesfluids.com)

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.00

