

ABS MUL[†]



BENEFITS

Forms a stable emulsion and reduces fluid loss

Does not need a secondary emulsifier package



APPLICATIONS

Performs with the ABS 40 system and other invert emulsion drilling fluid systems

1.0 gal/bbl (typical) for most applications



PHYSICAL PROPERTIES

- Appearance: Dark amber liquid
- Specific Gravity: 0.97
- Flash Point: 230°F

ABS MUL is a concentrated emulsifier that provides superior emulsion stability without the need for a secondary emulsifier package.



ABS MUL emulsifier

TREATMENT RECOMMENDATIONS

Typical concentrations of 1 gallon per barrel are sufficient for most applications. ABS MUL mixes easily with minimal agitation.

PACKAGING AND HANDLING

ABS MUL is available in 275 gal totes. Handle ABS MUL as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



AES DRILLING FLUIDS

www.aesfluids.com

☎ Phone : 281 556 5628

✉ Email : info@aesfluids.com

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.00

