

AES WA II[†]



BENEFITS

Preferentially oil-wets solids

Enhances and maintains emulsion stability while drilling



APPLICATIONS

1 gallon per 20 sacks of barite or 1 gallon per barrel of cuttings generated (typical)

Performs in conjunction with emulsifier and thinner additives

Pilot testing will aid to determine the appropriate concentration for a specific scenario



PHYSICAL PROPERTIES

- Appearance: Amber liquid
- Specific Gravity: 0.92 - 0.96
- Flash Point: >250°F
- Pour Point: -30°F

AES WA II is a wetting agent used with the ABS 40[†], AES VERT[†], or similar drilling fluid systems. It preferentially oil-wets drill solids, barite, and LCM additives.



AES WA II Wetting Agent

TREATMENT RECOMMENDATIONS

AES WA II is added at regular intervals while drilling to oil-wet drill cuttings and additives such as lost circulation or weight material. Add 1 gallon per barrel of cuttings generated or 20 sacks of barite added. Under extreme conditions, higher concentrations may be required.

AES WA II performs in conjunction with AES approved emulsifier packages and thinners and will disperse readily in the oil phase of fluid system.

Pilot testing recommended to determine the appropriate concentration for a specific scenario.

PACKAGING AND HANDLING

AES WA II is available in 5 gallon pails and 275 gallon totes. Handle AES WA II as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



AES DRILLING FLUIDS

www.aesfluids.com

☎ Phone : 281 556 5628

✉ Email : info@aesfluids.com

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.00

