

CHEMSEAL



BENEFITS

- Seals fractures, vugs, and porous zones
- Treats moderate to severe losses
- Does not alter fluid properties (inert solid)



APPLICATIONS

- 20 - 35 lb/bbl (typical) for sweeps
- Higher concentrations may be required for extreme conditions



PHYSICAL PROPERTIES

- Appearance: Cellulose and fibrous flake blend
- Specific Gravity: 1.43

Chemseal is a cellulosic fibrous blend of fine and medium flakes designed to control lost circulation in drilling fluids by forming a tightly packed seal in porous zones and fractures.



Chemseal lost circulation additive

TREATMENT RECOMMENDATIONS

Chemseal is a cellulose and fibrous material composed of medium and fine flakes designed to prevent and treat lost circulation by forming tightly packed barriers in severely porous and fractured zones.

When used in sweeps, typical concentrations range from 20 to 35 lb/bbl. When pumping high concentrations, consider pumping through open-ended pipe and/or remove any downhole screens before pill is pumped.

As with any lost circulation material, confirm that surface and downhole equipment will tolerate the distribution and concentration of particles present prior to use.

PACKAGING AND HANDLING

Chemseal is available in 40 lb sacks. Handle CHEMSEAL as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



AES DRILLING FLUIDS

www.aesfluids.com

☎ Phone : 281 556 5628

✉ Email : info@aesfluids.com

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.00

