

ENERVIS RM[†]



BENEFITS

Elevates low-end rheology to improve cuttings transport and minimize barite settling/sag risk

Performs in low-clay and conventional invert emulsion systems at low concentrations



APPLICATIONS

ENERVIS RM is designed for the EnerREACH[†] system

0.5 to 5.0 lb/bbl (typical) in conjunction with organophilic clay

Pilot test to determine appropriate concentrations for a specific application.



PHYSICAL PROPERTIES

- Appearance: Brown liquid
- Specific Gravity: 0.89 - 0.94

ENERVIS RM is a liquid rheology modifier that enhances low shear rate viscosity in EnerREACH and other invert emulsion systems.



ENERVIS RM rheology modifier

TREATMENT RECOMMENDATIONS

ENERVIS RM is a liquid additive used to prepare and maintain the EnerREACH system while drilling. Typical concentrations range from 0.5 to 5.0 lb/bbl, depending upon the base composition of the system.

Use caution adding ENERVIS RM at the rigsite. Avoid over-treating by starting with minimal additions of 0.1 - 0.2 lb/bbl and allowing sufficient time for product to yield. ENERVIS RM works in conjunction with organophilic clay.

PACKAGING AND HANDLING

ENERVIS RM is available in 5 gallon pails and 55 gallon drums. Handle ENERVIS RM as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



AES DRILLING FLUIDS

www.aesfluids.com

☎ Phone : 281 556 5628

✉ Email : info@aesfluids.com

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.00

