

ENERZAN L[†]



BENEFITS

Shear-thinning characteristics provide excellent carrying and suspension properties

Mixes easily at low shear and provides rapid dispersion without fisheyes

Stable across a wide range of pH levels



APPLICATIONS

0.06 - 0.7 gal/bbl (typical) for most applications

Can be added directly to well-agitated mud tank/pit or through hopper

Pilot testing will aid to determine the appropriate concentration for a specific scenario



PHYSICAL PROPERTIES

- Appearance: Tan colored liquid
- Specific Gravity: 1.08

ENERZAN L is a premium grade xanthan gum viscosifier dispersed in light mineral oil.



ENERZAN L liquid biopolymer

TREATMENT RECOMMENDATIONS

ENERZAN L mixes easily at low shear without developing fisheyes. ENERZAN L can be added directly to a well-agitated mud tank/pit or through the hopper. Typical concentrations range between 0.06 to 0.7 gal/bbl for most applications.

Pilot testing recommended to determine the appropriate concentration for a specific scenario.

PACKAGING AND HANDLING

ENERZAN L is available in 5 gal pails. Handle ENERZAN L as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



AES DRILLING FLUIDS

www.aesfluids.com

☎ Phone : 281 556 5628

✉ Email : info@aesfluids.com

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.00

