

ES-VIS[†]



BENEFITS

Natural, non-treated product contains no polymers or chemical additives

Provides a high yield point and low plastic viscosity

Optimum solids suspension and carrying capacity of solids



APPLICATIONS

15 - 25 lb/bbl for a base system with a 10:1 ratio of ES-VIS to ES-RM[†] for maintenance additions (typical)

Pre-hydrate in freshwater for best results

Pilot testing will aid to determine appropriate product concentration for the application



PHYSICAL PROPERTIES

- Appearance: Light tan powder
- Specific Gravity: 2.6

ES-VIS is a premium bentonite designed to provide an optimum viscosity profile in the EnerSEAL[†] fluid system.



ES-VIS premium bentonite viscosifier

TREATMENT RECOMMENDATIONS

For an initial blend, concentrations of ES-VIS range between 15 and 25 lb/bbl in most cases. Pre-hydration of ES-VIS in freshwater before blending a full EnerSEAL system will aid in product yield. During maintenance additions, a 10:1 ratio of ES-VIS to ES-RM is recommended.

Pilot testing recommended to determine the appropriate concentration for a specific scenario.

PACKAGING AND HANDLING

ES-VIS is available in 50 lb sacks. Handle ES-VIS as an industrial chemical, wearing protective equipment and observing precautions as described in the Safety Data Sheet (SDS).



AES DRILLING FLUIDS

www.aesfluids.com

☎ Phone : 281 556 5628

✉ Email : info@aesfluids.com

© 2020 AES Drilling Fluids. All rights reserved. The information provided is for informational purposes and is believed to be accurate, although this cannot be guaranteed. No guarantees or warranties are stated or implied. †Marks of AES Drilling Fluids, LLC.

Revision 1.00

